

HUBER Wash Drum RoSF9 / HUBER Sludge Acceptance Plant RoFAS



Efficient and reliable coarse material separation:

- Grit from WWTPs and sewer systems
- Road refuse and oil grit
- Septic sludge
- Industrial applications

►► Design and function

HUBER Wash Drum RoSF9 for separation of grit from WWTPs and sewer systems, road refuse and oil grit:

While wash water is added to pre-wash and homogenise the raw material within the HUBER Wash Drum RoSF9, the perforated plate of the Wash Drum retains all particles > 10 mm, which are dewatered and then discharged into a skip. Since only coarse material > 10 mm is separated, the volume of the resultant residues is vastly reduced with virtually the complete mineral material being further treated in the down-stream HUBER Coanda Grit Washer RoSF4. The resultant coarse material can then be further separated into a mineral and organic fraction by means of a coarse material washer.

HUBER Sludge Acceptance Plant RoFAS

Rotating high-performance screening drum for extreme applications. Reliable, clog-free solids transport through forced guided material transport within the drum. Solids washing and dewatering by means of a subsequent HUBER Wash Press WAP®.

►► Installation examples



HUBER Wash Drum for washout and separation of all coarse material > 10 mm

►► Benefits

- High solids throughput even with problematic material (tresses, grease, stones)
- High hydraulic capacity even with high solids contents
- Defined separation size due to two-dimensional screening
- Feeding from a conveyor, through a launder channel or pressure line
- Solids throughput up to 6 m³/h
- Completely encased unit
- Insensitive to coarse material
- 3 to 100 mm separation size
- Screened wastewater can be used as wash water
- Short tanker vehicle emptying times
- Optional simultaneous emptying of several vehicles
- Minimum wear, reduced maintenance
- Compact, space-saving design
- Low energy demand
- High corrosion resistance



50 l screenings removed per rotation

HUBER SE

Industriepark Erasbach A1 · D-92334 Berching
Phone: + 49 - 84 62 - 201 - 0 · Fax: + 49 - 84 62 - 201 - 810
info@huber.de · Internet: www.huber.de

Subject to technical modification
0,1 / 6 – 3.2020 – 7.2008

HUBER Wash Drum RoSF9 /
HUBER Sludge Acceptance Plant RoFAS