

➤ Double Stainless Steel Door TT1.2

Access door for buildings in the field of potable water supply and wastewater disposal with average security requirements.



The figure shown here may contain special accessories

Door, ready for installation, double door, double skinned, completely made from 1.4307 stainless steel (AISI 304 L), with double rubber seal, the door leaves and frame closing flush, the fixable and swing leaf opening to the outside (in escape direction).

Door leaves, skin: 1 mm, 55 mm thick, with injected CFCs-free polyurethane hard foam insulation, longitudinally ground surface finish, with rubber seal. Fastened to the frame with stable maintenance-free hinge plates. Mortise dead lock according to DIN 18251, class 3, with increased corrosion protection, stainless steel forend, provided for a customer-provided profile double cylinder (mechanical or digital), handle and cover of stainless steel.

The **fixable leaf** is operated by means of a sliding locking bolt. The contact surface between the opening leaf and fixable leaf is rubber sealed.

Frame, three-sided, fabricated from special section, with inserted rubber seal, with selectable sill closure, including fixing material.

Frame and door leaves shielded arc-welded and acid bath cleaned before washing, drying and surface passivation.

Ordering options:

Frame:

- Z-frame
- Block frame

Mounting:

- Embedded
- Bolted with dowelling clips
- Bolted through the frame (not to affect the finished wall)

Door opening options:

- Hinges on left
- Hinges on right

Sill closure:



- With step flashing
- Without step flashing

Options:

- 1.4404 (AISI 316 L) stainless steel
- Panic lock
- Upper door closer, lockable in position
- One-part or two-part door arrestor
- Surface finish (lacquer with or without anti-graffiti properties, copper covering, wooden panelling)
- Electronic monitoring options (alarm system in door surface, magnetic contact, lock-bolt contact, block lock)
- Door heating (heating cable in frame and/or door surface), without temperature sensor, without controls
- Potential equalisation on frame
- Security ventilation louvres, openings to admit light
- Steel sheet finish for exterior door surface for installations exposed to sunlight


Note:

If the door is exposed to sunlight, its operability may be affected. In such a case, it is recommended to equip the door outside with a wood panelling or steel sheet.



Stockrahmen
 stock frame

Z-Zarge
 Z-frame



We manufacture to your specifications. Please consider these definitions of measures:

Clear wall opening (F) = distance between bottom edge of lintel and top edge of unfinished floor

Clear height (H) = distance between bottom edge of lintel and top edge of finished floor

HUBER SE

Industriepark Erasbach A1 · D-92334 Berching
 Phone: + 49 - 84 62 - 201 - 0 · Fax: + 49 - 84 62 - 201 - 810
 info@huber.de · Internet: www.huber.de

Subject to technical modification
 Drawing No. 190.160, 5.2022

Double Stainless Steel Door TT1.2