

[Home](#) ■ [Products](#) ■ [Conveyors](#)

## HUBER Launder Channel HLC



### Feed system for screenings wash presses

- Wastewater or service water as flushing water
- Up to 30 m channel length
- High operating reliability, low maintenance requirements
- Customised solutions

The HUBER Launder Channel operates discontinuously in a batch mode or continuously. The screenings to be treated drop into the launder channel from one or several screens. Wastewater or service water is used to flush the screenings into the wash press. The flushing water serves also as wash water for screenings washing.

HUBER Launder Channels can be adjusted to suit customer-specific requirements. To ensure maximum operating reliability the launder channel control system can be designed to use redundant wash press systems and operate the individual units as needed via according valve control.

### Benefits

- Cost-effective, low maintenance solution

- High operational reliability
- Up to 30 m channel length
- Wastewater or service water as flushing water
- Stainless steel design for corrosion resistance

## Downloads

 [Brochure: HUBER Launder Channel HLC](#) [pdf, 480 KB]

## Case Studies

- [Charfield STW Case Study: Inlet Screen Replacement Project](#)
- [Conveyor technology made by HUBER SE: Indispensable and reliable](#)
- [Start-up of the equipment for preliminary mechanical wastewater treatment on WWTP Atotonilco](#)
- [Wash Press WAP® L for Launder Channel Feed: Meadowhead's success leads to subsequent orders from Scottish Water](#)
- [Dewatering and Compacting and Compacting of Reject from Food Waste AD Plant](#)
- [A successful combination: Launder Channel plus Wash Press SL](#)

## Media



Video: HUBER Launder Channel HLC

<https://www.youtube.com/watch?v=g-aczj1GDtY>

## More products of this group: Conveyors

- [HUBER Screw Conveyor Ro8 / Ro8 T](#)

Adresse / address: HUBER SE · Industriepark Erasbach A1 · 92334 Berching · Germany · Telefon / phone: + 49 - 84 62 - 201 - 0 · Fax / fax: + 49 - 84 62 - 201 - 810  
e-mail: [info@huber.de](mailto:info@huber.de) · Internet: <http://www.huber.de>

Sitz der Gesellschaft / Headquarters: Berching · AG Nürnberg / Register of companies: HRB 25558

Vorstand / Board: Georg Huber (Vorsitzender / CEO), Dr.-Ing. Oliver Rong (stellvertretender Vorsitzender / Vice CEO), Dr.-Ing. Johann Grienberger, Rainer Köhler  
Aufsichtsratsvorsitzender / Chairman of the Supervisory Board: Alois Ponnath

USt (VAT)-IdNr.: DE 812353219

Bank: HypoVereinsbank Nürnberg (BLZ 760 200 70) 5 008 409 · SWIFT-BIC: HYVEDEMM460 · IBAN: DE 30 7602 0070 0005 0084 09

