

[Home](#) ■ [Solutions](#) ■ [Energy Efficiency](#) ■ [Sludge Treatment](#) ■ [Screening](#)

## Energy-Efficient Sludge Screening





Sludge screening is recommended where:

- screens in the headworks are not fine enough,
- sludge, e.g. septic sludge, is imported,
- clogging of sludge treatment components, e.g. heat exchangers, must be prevented,
- certain solids could impair treatment or reuse of treated sludge.

Our ROTAMAT® Sludge Screen Ro 3.1 has a bar spacing of 6 or 8 mm. Sludge, e.g. imported septic sludge, flows through the screen by gravity. Removed screenings are washed and compacted to 30 – 45 %DS. Power consumption is 10 – 20 Wh/m<sup>3</sup>.

Sludge is pumped through perforations of our [STRAINPRESS® Sludgecleaner](#). Their diameter is 3 – 10 mm, most commonly 5 mm. The Strainpress also removes hair and fibres and compacts the screenings to 35 – 45 %DS. Its power consumption, including pumping, is around 50 Wh/m<sup>3</sup>.

Adresse / address: HUBER SE · Industriepark Erasbach A1 · 92334 Berching · Germany · Telefon / phone: + 49 - 84 62 - 201 - 0 · Fax / fax: + 49 - 84 62 - 201 - 810  
e-mail: info@huber.de · Internet: http://www.huber.de

Sitz der Gesellschaft / Headquarters: Berching · AG Nürnberg / Register of companies: HRB 25558  
Vorstand / Board: Georg Huber (Vorsitzender / CEO), Dr.-Ing. Oliver Rong (stellvertretender Vorsitzender / Vice CEO), Dr.-Ing. Johann Grienberger, Rainer Köhler  
Aufsichtsratsvorsitzender / Chairman of the Supervisory Board: Alois Ponnath

USt (VAT)-IdNr.: DE 812353219

Bank: HypoVereinsbank Nürnberg (BLZ 760 200 70) 5 008 409 · SWIFT-BIC: HYVEDEMM460 · IBAN: DE 30 7602 0070 0005 0084 09

